


UM-1 UM-5



Description:

- Low Cost
- Wide Frequency Range
- Excellent Aging
- AT Cut Crystal
- Communication Equipment

Performance Characteristics

Parameter		UM-1	UM-5
Frequency Range (MHz)	F ₀	8~40	30~100
Mode of Vibration Mode		Fundamental	3rd Overtone
Resonance Resistance (Ω)	R _r	60	60
Frequency Tolerance (at 25°C)		±3×10 ⁻⁶ ~±15×10 ⁻⁶	
Storage Temperature Range	T _{STG}	-55°C~+125°C	
Shunt Capacitance	C ₀	7pF Max	
Load Capacitance	CL	6pF~100pF or Series	
Insulation Resistance	IR	>500MΩ DC/100V±10V	
Drive Level	DL	0.01mW~0.1mW	
Aging	Fa	±3×10 ⁻⁶ ~±5×10 ⁻⁶ /year	

Frequency Stability Over Temperature Range

Temperature Range	Frequency Stability						
	M:±3×10 ⁻⁶	N:±5×10 ⁻⁶	O:±10×10 ⁻⁶	P:±15×10 ⁻⁶	Q:±20×10 ⁻⁶	S:±30×10 ⁻⁶	T:±50×10 ⁻⁶
A:0°C~+50°C	●	●	●	●	●	●	●
B:-10°C~+60°C		●	●	●	●	●	●
C:-20°C~+70°C		●	●	●	●	●	●
G:-40°C~+85°C			●	●	●	●	●
J:-55°C~+125°C							※

※: Specially designated products.

Outline Drawing (mm)

